



TECHNICAL DATA

Order no.	82295.6
Certified to	EN 997 / EN 33
Specification	rimless Washdown for min. 4,5/3-l-flush back to wall
Outlet	horizontal vertical 70 and 110 mm
Weight	25,0 kg
Accessories excl.	Floorstanding cistern Universal, order no. 82866.0, 82866.1, 82866.3, 82866.4 Seat and cover, order no. 89395.5, 89695.0, 89896.5 Seat and cover with automatic lowering system, order no. 89160.1, 89395.9, 89695.1, 89896.6
Mounting acc. incl.	Fixing set, order no. 89175.7
Mounting acc. excl.	for horizontal outlet use standard variable connection for outlet vertical 70 mm LAUFEN-connection set, order no. 89009.2

Mounting acc. excl. for outlet vertical 110 mm LAUFEN-connection
set, order no. 89902.7

Colours see colour table

SPECIFICATION TEXT

Floorstanding WC pan rimless washdown LAUFEN PRO
sanitary ceramic,
for concealed cistern and floorstanding cistern Universal
EN 997, EN 33, min. 4,5/3-l-flush, dimensions 360 x 530 x 430 mm
outlet horizontal, vertical 70 and 110 mm
back to wall, concealed fixation
Special feature: rimless, concealed surfaces directing water are fully
glazed throughout, vacuum checked
Further options / accessories: Surface refinement LCC (only white),
floorstanding cistern Universal 82866.0, 82866.1, 82866.3, 82866.4,
WC seat and cover, 89395.5, 89695.0, 89896.5, WC seat and cover with
automatic lowering 89160.1, 89395.9, 89695.1, 89896.6
Order no. 82295.6

TECHNICAL DRAWINGS / S 1 : 20

