


WC-SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922461
Collection	ViConnect
PROJECTS	 PLUS
Width	525 mm
Height	1120 mm
Depth	135 mm
Weight	14 kg
description	<p>for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, depth adjustment front edge of element: 135-205 mm</p> <p>incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate</p> <p>tested in accordance with DIN EN 14055</p> <p>packaged in a box</p> <p>For combination with: for wall-mounted WC</p> <p>self-supporting powder-coated steel frame, fully pre-assembled, front operated, with small inspection opening</p> <p>concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, filling valve Noise Class I, 2-part angle valve connection set R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, adjustable flush flow control for adaptation to rimless toilet bowls, certification marks for concealed cistern: Noise Class I for dry-wall construction, standard height</p>

Specification texts

ViConnect; Toilet installation system; Size: 525 x 1120 x 135 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, depth adjustment front edge of element: 135-205 mm; incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate; tested in accordance with DIN EN 14055; packaged in a box; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled, front operated, with small inspection opening; concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, filling valve Noise Class I, 2-part angle valve connection set R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, adjustable flush flow control for adaptation to rimless toilet bowls, certification marks for concealed cistern: Noise Class I; for dry-wall construction, standard height

COLOURS

92246100 4051202339630

TECHNICAL DRAWINGS

922461

