


WC-SYSTEM FOR BRICK-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922483
Collection	ViConnect
PROJECTS	 PLUS
Width	528 mm
Height	735 mm
Depth	124 mm
Weight	3,41 kg
description	installation depth 124 mm with fixing brackets, flushing pipe connector, without fastening materials, without flush plate Individual packaging materials For combination with: for wall-mounted WC, for floor-standing WC, back to wall front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint, with protection cap for the flushing pipe concealed cistern with insulation against condensation with dual flush 3/6 l, adjustable to 3/4, 5 l, maximal flush quantity 7,5 l, filling valve Noise Class I, 2-part angle valve connection set R1/2, protection box for access opening, flushing pipe bend with protection cap, certification marks for concealed cistern: Noise Class I,



PROJECTS

Specification texts

ViConnect; Concealed cistern; Size: 528 x 735 x 124 mm; installation depth 124 mm; with fixing brackets, flushing pipe connector, without fastening materials, without flush plate; Individual packaging materials; For combination with: for wall-mounted WC, for floor-standing WC, back to wall; front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint, with protection cap for the flushing pipe; concealed cistern with insulation against condensation with dual flush 3/6 l, adjustable to 3/4,5 l, maximal flush quantity 7,5 l, filling valve Noise Class I, 2-part angle valve connection set R1/2, protection box for access opening, flushing pipe bend with protection cap, certification marks for concealed cistern: Noise Class I,

COLOURS

92248300 4051202338275

TECHNICAL DRAWINGS

922483

